



**Totaalleverancier
van lasers en medische
technologieën**



Laservision Instruments BV
+31 (0) 529 428 000

www.laservision.nl
info@laservision.nl

Phoroptar[®] VRx
AMETEK REFRACTOR SYSTEM

Reichert
TECHNOLOGIES
AMETEK

DRIVE PRACTICE EFFICIENCY
WITH PHOROPTOR[®] VRx



NEW PHOROPTOR[®] VRx
DIGITAL REFRACTION SYSTEM

Reichert[®]
TECHNOLOGIES
AMETEK[®]



Drive practice efficiency and accelerate your exam process. Phoroptor® VRx Digital Refraction System easily adapts to your practice, allowing you to rapidly perform all of the functions of a manual Phoroptor®, and so much more, while comfortably seated next to your patient.

Phoroptor VRx sets new standards in digital refraction. With the thinnest, most compact design available, incredibly fast lens exchanges, motorized prisms, split cylinder lenses, and ultra-quiet operation, Phoroptor VRx offers an outstanding patient experience.

The touchscreen display and ergonomic keypad features a multi-function control knob with unmatched feel and versatility. The intuitive interface has all the pre-programmed and programmable tests you'll need for an exceptional user experience.

Phoroptor VRx connects to EMR systems as well as numerous models of pre-test and acuity devices from both Reichert and non-Reichert brands, for effortless integration.



Phoroptor VRx is made in the USA. 



The most advanced Phoroceptor® ever built.

Phoroceptor® VRx

Inventing and reinventing.

Reichert's legacy in refraction continues.

For over 90 years, the Phoroptor® name has been synonymous with the world's finest refracting instrument. Phoroptor® VRx continues with the same legendary engineering, quality, craftsmanship, and reliability – now with the speed and efficiency of a digital refraction.



Smallest design. Biggest impression.

See more of your patient. See more patients.

With the most compact digital refractor head available (12.2 W × 8 H × 2.8 D in. at a 64 mm PD), Phoroptor VRx is non-intimidating and allows for greater patient visibility. The sleek, refined and high-tech styling of Phoroptor VRx will impress all your current patients and help gain new ones.



Impressively thin.

Thinnest Phoroptor yet.

To prevent patients from experiencing tunnel vision, Phoroptor VRx has the thinnest lens profile amongst digital refractors, at 26 mm. In fact, Phoroptor VRx has a thinner profile than a manual Phoroptor.



Retractability.

Unique prism lenses.

To achieve the thinnest lens profile, Phoroptor VRx has external motorized prism lenses that slide in and out only as needed.





Refined interior & exterior.

Premium parts and assembly.

Premium motors and metal housing provide Phoroptor VRx with incredibly fast and ultra-quiet lens exchanges. Unlike other digital refractors, your patients will hardly notice the lens movement. Phoroptor VRx is designed and hand-assembled by skilled technicians in Buffalo, New York, USA.

More cylinders. More horsepower.

Jackson Cross Cylinder, Smart Cylinder, and Split Cylinder.

Refinement of cylinder power and axis can be accomplished using the familiar Jackson Cross Cylinder or the innovative Smart Cylinder method where cylinder power and axis are automatically bracketed based on the amount of cylinder in the patient's prescription. Phoroptor VRx also features a Split Cylinder mode, where patients are simultaneously presented with two targets.



Selectable drive modes.

Pre-programmed & programmable tests.

To increase efficiency and allow refraction to be delegated to trained technicians, Phoroptor VRx has pre-programmed and programmable test options. You can choose from pre-programmed tests including astigmatism, phoria, binocular balance, and near vision. Customize up to four user programmable sequences that can be easily modified or conveniently shared between multiple Phoroptor VRx systems.



Automatic headlights.

Illuminated near point.

The RotoChart near point card is automatically illuminated, with two available brightness levels, when the reading rod is lowered into position.



Precise handling and control.

Logical keypad design.

The Phoroceptor VRx controller features a logically and ergonomically arranged keypad, designed to enhance the user experience. Buttons are grouped based on functionality for easy access: gray for data, blue for refraction, and black for acuity. Buttons are also LED backlit for better visibility in dimly lit exam rooms.



Multi-function knob.

The Phoroceptor VRx multi-function control knob is smooth rotating and has a solid feel comparable to the Ultramatic RX Master™ Phoroceptor® dials you know and love, for unmatched control knob versatility.



Instant comparison.

Quickly compare prescriptions.

With a single touch, switch between final, subjective, unaided, auto refractor, or lensmeter data, allowing your patient to instantly visualize the difference in prescriptions.



Your digital dashboard.

10.4 inch touchscreen display.

You can access all functions and settings of the intuitive user interface, through the integrated 10.4 inch tilting, touchscreen display.



Well connected & plays well with others.

Connectivity to pre-screening and acuity devices.

Phoroceptor VRx seamlessly connects to Reichert lensmeters, auto refractors, and acuity systems, such as ClearChart 2 and ClearChart 3P, along with a comprehensive list of non-Reichert compatible devices. (See Specifications)



Bluetooth® comes standard.

Wirelessly connected.

Bluetooth is built into the Phoroceptor VRx Central Unit and Reichert Bluetooth adapters (see Specifications) can be paired to connect an external instrument wirelessly.



Effortless integration.

EMR compatibility.

Phoroceptor VRx integrates with an extensive list of EMR systems, removing the risk of transcription error and increasing patient throughput. Phoroceptor VRx can take advantage of an EMR system's capability of bi-directional communication, allowing you to import and export refraction data.



Phoroptor® VRx Digital Refraction System

System includes Phoroptor VRx Head Assembly, Controller, and Central Unit.

16241 Phoroptor VRx , Middle Mount

16242 Phoroptor VRx with Prism, Middle Mount



Standard Included Accessories

Dust Cover- Phoroptor Head	Power Cord 115V or Power Cord 230V
Dust Cover- Controller Assembly	
Phoroptor Cable	
User Guide Shield Kit (2 sets)	
Decimal Card Holder or Snellen Card Holder	Quick Reference

Optional Accessories

16230 Thermal Printer	
16205 Phoroptor VRx Controller Table	
16250 Wireless Dongle Kit	Bluetooth Connection to ClearChart 3P, AL200
16251 Wireless Dongle Kit	Bluetooth Connection to ClearChart 2
16253 Wireless Dongle Kit	Bluetooth Connection to AP250, AL700, RK700
16254 Wireless Dongle Kit	Bluetooth Connection to RK600
16255 Wireless Dongle Kit	Bluetooth Connection to AL500, Computer
16233 Wireless Dongle	Single Bluetooth Dongle

Specifications:

Phoroptor Head Assembly

Spherical Effects	+17.75 to -22.25 D, Steps 0.25 or 1.00 D
Cylinder Power	+8.0 to -8.0 D, Steps 0.25 or 1.00 D
Axis Adjustment	0 to 180°, Steps 1°, 5°, or 10°
Cross Cylinder Test	± 0.25 D
Corneal Vertex Distance	16 mm

Prismatic Effects (Optional) Steps	+0.20 Δ +0.25 Δ , +0.50 Δ
Pupil Distance	50 to 80 mm, Steps 1 mm Binocular
Convergence	400 mm
Height Level of Eyes, Adjustment	\pm 3 mm
Leveling	Via Bubble Level
Free Aperture	19 mm
Thickness of Housing at Viewing Aperture	26 mm
Width \times Height \times Depth (at PD = 64mm)	31 \times 20.3 \times 7.1cm (12.2 \times 8 \times 2.8 in.)
Weight w/ Mount, w/o Prism Compensator	4.42 kg (9.75 lb)
Weight w/ Mount, w/ Prism Compensator	4.65 kg (10.25 lb)
Weight w/o Mount, w/o Prism Compensator	3.95 kg (8.70 lb)
Weight w/o Mount, w/ Prism Compensator	4.17 kg (9.20 lb)

Controller with Display

Controller Width \times Height \times Depth	23.4 \times 4.6 \times 16.8 cm (9.9 \times 1.5 \times 6.9 in.)
Display Width \times Height \times Depth	22.4 \times 15.7 \times 1.5 cm (10 \times 7 \times 2.8 in.)
Display Size Diagonal	10.4 in. (1024 x 768 Pixel Resolution)
Weight	2.9 kg (6.4 lb)

Central Unit

Width \times Height \times Depth	20.1 \times 8.9 \times 26.7 cm (7.9 \times 3.5 10.5 in.)
Weight	3.2 kg (7.1 lb)
Input Voltage	100 - 240V~
Frequency	50 - 60 Hz
Current (Max.)	60 VA
Fuses	T2AL 250V
Ports (1 Each)	Phoroptor, Controller (Keypad), Projector (Acuity System), Printer, Instrument 1 I/O, Instrument 2 I/O, EMR Port, Transfer Port

EMR System and External Device Compatibility

For a current list of EMR systems, Reichert, and non-Reichert devices that are compatible with Phoroptor VRx, view the product specifications at www.reichert.com.

DRIVE PRACTICE EFFICIENCY WITH PHOROPTOR® VRx

The most advanced Phoroptor® ever built.
www.reichert.com/vrx



Reichert®
TECHNOLOGIES

AMETEK®

© 2015 AMETEK, Inc. & Reichert, Inc. 16241-110-Rev A www.reichert.com



De Grift 20
7711 EJ, Nieuwleusen

www.laservision.nl | info@laservision.nl | 0529 - 428000 | [@laservision_instruments](https://www.instagram.com/laservision_instruments)